



# MX-PRO® R3

## x-frame ambulance cot

stryker®



### EMS Equipment

3800 E. Centre Ave.  
Portage, MI 49002 U.S.A.  
t: 269 329 2100 f: 269 329 2315  
toll free: 800 784 4336

www.ems.stryker.com

### Standard Features

- Transport at load height capability
- Positive action height adjustment
- Easy-to-use release handle design
- Color-coded controls
- Dampened action during hot drops
- High visibility powder-coated frame
- Lightweight, rugged aluminum construction
- Scientifically optimized lift bar design
- Lower lifting bar
- Seven height positions
- Integrated bumper system
- Lift-capable safety bar
- Perforated litter surface
- One-hand release breakaway head section with safety bar
- Floor-mounted safety hook
- One-hand release, fold down side rails
- One-hand release, infinite positioning, pneumatically assisted backrest
- Oversized wheels with sealed caster and wheel bearings
- Reflective labeling
- Sealed bolster mattress
- Shock positioning
- Two lap belts and one four-point shoulder restraint
- Single wheel lock

### Optional Features

- Heavy duty two- or three-stage IV poles (patient right or left)
- Base lift bar
- Hard or soft base storage
- High height kit for 33 inches
- Defibrillator platform
- Pocketed or nonpocketed head end storage
- Height limit kit\*
- Permanent or removable O<sub>2</sub> bottle holders (head or foot end)
- Pull handle
- Sealed flat mattress
- Premium mattress
- Dual wheel lock
- X-frame guards
- Head extension with pillow
- Pillow only
- Rigid head end storage tray
- Equipment hook
- Backrest storage pouch

### Specifications

<b>Model Number</b>	<b>6082</b>
<b>Height<sup>1</sup></b>	
Position 1	13.5 in. (34 cm)
Position 2	21 in. (53 cm)
Position 3	25.5 in. (65 cm)
Position 4	29 in. (74 cm)
Position 5	32 in. (81 cm)
Position 6	35 in. (89 cm)
Position 7	37.5 in. (95 cm)
<b>Length</b>	
Standard	80.5 in. (205 cm)
Minimum	62 in. (158 cm)
<b>Width</b>	23 in. (58 cm)
<b>Weight<sup>2</sup></b>	81 lb. (38 kg)
<b>Wheels</b>	
Diameter	6 in. (15 cm)
Width	2 in. (5 cm)
<b>Articulation</b>	
Backrest	2° – 73°
Shock Position	+14°
<b>Maximum Weight Capacity</b>	650 lb. (295 kg)
<b>Minimum Operators Required</b>	
Occupied Cot	2
Unoccupied Cot	1
<b>Recommended Fastener System</b>	
Floor Mount	Model 6370, 6377 or 6378
Wall Mount	Model 6371
<b>Recommended Loading Height*</b>	Up To 32 in. (81 cm)

### Warranty

- One year parts, labor and travel or two years parts

\*Height limit kit recommended for load heights less than 28 inches (71 cm). High height kit recommended for load heights more than 32 inches (81 cm).

<sup>1</sup> Height measured from bottom of mattress at seat section to ground level.

<sup>2</sup> Cot is weighed without mattress and restraints.

Stryker reserves the right to change specifications without notice.

In-service video included with every order.

The MX-PRO R3 is designed to conform to the Federal Specification for the Star-of-Life Ambulance KKK-A-1822.

The MX-PRO R3 is designed to be compatible with competitive cot fastener systems.

The yellow and black color scheme is a proprietary trademark of the Stryker Corporation.

